



**Installation Instructions
1984-1995 XJ (Cherokee)
Rear Tube Bumper
P/N: 11570.80**

Hardware: (2) Left and right mounting plates
(4) Hex head mounting bracket bolts
(8) Flat Washers
(4) Lock Washers




NOTE!

To obtain correct installation, we recommend that you follow the basic steps covered in these instructions. Please take care when assembling this product to protect the finish and to maintain a quality look to your new investment. If able have a second person help with the installation.

Step (1): A 15mm deep socket will be needed to remove the (8) factory mounting bolts from the XJ body (4 for each side). There is no need to remove the rear bumper cover.
Do Not Discard These Bolts. They Are To Be Reused.

Step (2): Install supplied tube bumper mounting brackets to the left and right side of the unitized frame. Align mounting brackets using supplied template.

**Bracket tube bumper outer mounting face.
Must be .75" from center of outer mounting holes
or 40.25" (1022.35mm) apart when mounted**





- Step (3):** Attach the tube bumper to the mounting bracket at the lower mounting holes using the supplied 18mm bolt, washer, and nut. **DO NOT TIGHTEN.** Have another person hold one side of the bumper during this step to avoid damage to the bumpers finish. Repeat step three for the other side. **DO NOT TIGHTEN.**
- Step (4):** Install the upper 18mm mounting bolts to the bumper and mounting plate. With all 4 bolts installed tighten bolts to allow just enough movement of the bumper to allow proper alignment. Check clearance of the rear door when closing. Adjust as needed.
- Step (5):** When all adjustments have been made tighten all bolts to secure rear bumper in correct position.



LIMITED 90 DAY WARRANTY

Applies to Rugged Ridge by Omix-ada Inc. Products

Rugged Ridge Off Road (the Company) warrants to the original purchaser of this product that should the product or any part thereof, under normal use and conditions, be proven defective in material or workmanship within 90 DAYS from the date of original purchase, such defect(s) will be repaired or replaced or credited at the Company's sole option.

To obtain repair or replacement within the terms of this Warranty, the product is to be delivered with proof of warranty coverage (e.g. Dated bill of sale), specification of defect(s) to the place of purchase or, with prior approval from the Company (Return Authorization Number is required), freight pre-paid to the Company address listed below.

This warranty does not apply to any product or part thereof which, in the opinion of the Company, has suffered or been damaged through alteration, improper installation, mishandling, misuse, neglect, accident or by acts of nature. THE EXTENT OF THE COMPANY'S LIABILITY UNDER THIS WARRANTY IS LIMITED TO THE REPAIR OR REPLACEMENT PROVIDED ABOVE AND, IN NO EVENT, SHALL THE COMPANY'S LIABILITY EXCEED THE PURCHASE PRICE PAID BY PURCHASER FOR THE PRODUCT.

This Warranty is in lieu of all express warranties or liabilities. ANY IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, SHALL BE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY MUST BE BROUGHT WITHIN THE PERIOD OF 90 DAYS FROM DATE OF ORIGINAL PURCHASE.

IN NO CASE SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WHATSOEVER. No person or representative is authorized to assume for the Company any liability other than expressed herein in connection with the sale of this product.

Some States do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, so the above limitations may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Omix-ada Inc.
460 Horizon Dr. Suite 400
Suwanee, Georgia 30024

